NATIONAL-SPENCER, INC.

ZEE LINE LUBRICATION EQUIPMENT

Phone 800-231-1525

Fax 800-637-9511

Web Address www.zeeline.com





Features

- Adjustable waste oil drain with minimum height 55 inches and maximum height 75 inches
- 23-gallon wheel mounted tank with front and rear ball bearing wheels (3" front casters and 6" rear wheels)
- Centrally mounted bowl on swivel joint for positioning
- Maximum collection capacity without draining is 19.7 gallons
- 22.5 inch diameter oversize funnel
- 3.5 gallon capacity collection bowl with adjustable height
- 6.5 foot long drain hose
- 7 PSI maximum draining air pressure
- Level sight gauge: Scale in litres and gallons
- Anti-splash screen/filter provides useful support for draining used filters
- Removable steel tool tray

Applications/Instructions

- For gravity drain of fluids from engines, gearboxes or differentials of all motor vehicles placed on an auto-lift or pit.
 - To evacuate tank:
 - 1) Close all valves and raise funnel tubes up until it snaps
 - 2) Apply air to the tank
 - 3) Once the tank has pressurized, roll the tank to where you want to discharge the old oil
 - 4) Place drain tube in new container
 - 5) Open the valve at the opposite end of the drain hose

Number of boxes and contents

- □ Tank (1 box), 17.5" x 18.5" x 34" (75 pounds)
- □ Funnel and tube (1 box), 24" x 24" x 11" (23 pounds)
- □ UPC Code 0 1595441236 6